



WP-F1

Direct Thermal Barcode Printer

- 152mm per second high printing speed
- Open assess for easy media loading
- Auto-calibration of media
- Head-up sensor and platen replacement
- Free bundled labeling software and windows drivers



Storage




Supermarket



Medical



POST



F1

Direct Thermal Barcode Printer



Model F1	
Resolution	203 DPI
Print method	Direct Thermal
Print speed	152mm(6'')/s Max.
Max.print width	104 mm (4.25")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20 ~ 118 mm (0.78 " ~ 4.6 ")
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Media core diameter	25.4 ~ 76.2 mm (1 " ~ 3 ")
Label length	10~1778 mm (0.39"~70")
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	USB (Optional:Lan/Serial/ WIFI/Bluetooth/TF card)
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°、90°、180°、270°
Emulaion	TSPL、EPL、ZPL、DPL
Physical Features	
Dimension	240(D) x 212(W) x172(H)mm
Weight	2.15kg
Reliability	
Warranty	One year for the printer
Print head	30 km
Software	
Driver	Windows / Linux / Mac
SDK	Windows / iOS / Android
Power supply	
Input	AC 100-240V,1A, 50-60Hz
Output	DC 24V, 2.5A, 60W
Options	
Factory Options	① Peeling machine ② Bluetooth ③ WIFI ④ Serial
Dealer Options	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder ③ Shipment waybill box
Environmental Conditions	
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing

